

EXPANDED METAL

Steel

Flattened Expanded Metal

Style Designation	Lbs./sq.ft.	Size of Opening in Inches		Center to Center of Bridges in Inches		Aprox. Thickness of Strand in Inches
		Width	Length	Width	Length	
1/4" -18-20	1.11	3/32	11/16	.255	1.031	.040
1/2" -18-20	0.66	9/32	1	.500	1.260	.039
1/2" -16-18	0.82	1/4	1	.500	1.260	.050
1/2" -13-15	1.4	1/4	1	.500	1.260	.070
3/4" -16-18 Hy	0.51	3/4	1 3/4	.923	2.100	.048
3/4" -13-15	0.75	11/16	1 25/32	.923	2.100	.070
3/4" -9-11	1.71	9/16	1 11/16	.923	2.120	.120
1 1/2" -13-15	0.57	1 1/16	2 3/4	1.330	3.200	.070
1 1/2" -9-11	1.14	1	2 9/16	1.330	3.200	.110

Expanded Metal

Style Designation	Lbs./sq.ft.	Size of Opening in Inches		Center to Center of Bridges in Inches		Size of Strands in Inches		
		Plain	Width		Width	Length	Width	
1/2" - 13	1.47		5/16	15/16	.500	1.2	.092	.096
3/4" 16 Hy	0.54		13/16	1 3/4	.923	2.0	.060	.101
3/4" - 13	0.8		3/4	1 11/16	.923	2.0	.092	.096
3/4" - 9	1.8		11/16	1 9/16	.923	2.0	.134	.150
1 1/2" - 9	1.2		1 1/8	2 3/8	1.330	3.0	.134	.144
1 1/2" - 6	2.5		1	2 5/16	1.330	3.0	.198	.203